



## WEIGHING INSTRUMENTATION

### weight transmitters

#### UWT 6008

From the Pavone Sistemi experience here it is the UWT 6008, unique product in the family of weight transmitters: from 8 (eight) load cells to the instrument without using the junction box.

Ideal for all industrial applications where it is necessary to know the load distribution on the different load cells.

Able to monitor all load cells and generate alarms due to excessive cell signal drift, missing connections, failure of one of the cells, unbalanced weight distribution.

The emulative control allows the continuity of work of the weighing system even in case of failure on one of the load cells, until the replacement of the same.

A particular algorithm allows to equalize the angles of the scale with just one passage of the sample weight

Availability of all FIELDBUS and Analog output at the same time

#### TECHNICAL CHARACTERISTICS UWT 6008

|                               |  |
|-------------------------------|--|
| Transducers power supply:     | 5 Vdc (max. 230 mA)  |
| Measuring range:              | -3.9 ÷ +3.9 mV/V   |
| Input sensitivity:            | Min. 0.02 microV   |
| Linearity:                    | < 0.01% FS   |
| Thermal drift:                | < 0.001% FS/ °C  |
| Display:                      | 128 x 64-pixel graphic LCD   |
| A/D converter:                | 24 bits  |
| Internal resolution:          | > of 16,000,000 points   |
| Signal capture frequency:     | 12.5 ÷ 300 Hz  |
| Displayable resolution:       | 999,999 divisions viewable on the net weight   |
| Divisions value (selectable): | x1, x2, x5, x10, x20, x50  |
| Settable decimals:            | 0.0 ; 0.00 ; 0.000 ; 0.0000  |
| Filter:                       | selectable 5 ÷ 250 Hz  |
| Device power supply:          | 12-24 Vdc ± 15% - power consumption 4 W  |
| Operating temperature:        | -10/+ 50°C (max. humidity: 85% without condensation)   |
| Storage temperature:          | -20/+70°C  |
| Logical outputs:              | 2 relays, Max. 48 Vac/Vdc, 2A each   |
| Logical inputs:               | 2 opto-isolated at 12/24 Vdc PNP (external power supply)   |
| Serial ports:                 | 1 USB device + 1 RS232C + 1 RS485  |
| Optional analog output:       | 16-bit opto-isolated Voltage: 0 ÷ 5/10 V (min. R: 10 K Ohm), Current: 0/4 ÷ 20 mA (max. R: 300 Ohm). |
| Analog output linearity:      | < 0,02% FS   |
| Analog output thermal drift:  | 0,001% FS / °C   |
| Microcontroller:              | ARM Cortex M0+ at 32 bits, 256KB Flash reprogrammable on-board from USB                              |
| Data memory:                  | 64 Kbytes expandable up to 1024 Kbytes   |
| Compliance with regulations:  | EN61000-6-2, EN61000-6-3 for EMC; EN61010-1 for Electrical Safety, EN45501 for metrology             |
| Dimensions:                   | 100 x 75 x 110 mm (L x H x P)  |



