



额定载荷 (t)	D1	D2	D3	D4	H1	H2	H3	H4	H5
10	∅50	∅40	∅138	M20X1.5	17	35	74	134.5	20.55
20、25	∅65	∅40	∅165	M24X1.5	25	50	87	161	20.55
30	∅75	∅50.8	∅165	M30X1.5	25	55	86	176	21
40	∅85	∅76.2	∅165	M40X1.5	25	65	95.8	221	25.4



仓储秤、实验机  
warehouse scale, experimental machine

### TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	10、20、25、30、40t	输出阻抗 Output resistance	352 ± 3 Ω
精度等级 Accuracy class	0.05 (10~25t) 0.1 (30~40t)	绝缘电阻 Insulation resistance	≥5000 MΩ
灵敏度 Sensitivity	3.0 ± 0.006mV/V	额定温度 Nominal Temp Range	-10~+40℃
线性误差 Non-linearity	±0.05% (10~25t) F.S	工作温度范围 Service Temp Range	-30~+70℃
	±0.1% (30~40t) F.S	安全负载 Safe load limit	120%F.S
滞后误差 Hysteresis error	±0.05% (10~25t) F.S	破坏负载 Breaking load	150%F.S
	±0.1% (30~40t) F.S	额定激励电压 Nominal of range excitation	10~12V DC
蠕变 (30分钟) Creep(30min)	±0.02%F.S	密封等级 Protection Class	IP67
零点温度影响 TC ZERO	±0.02%F.S/10℃	材料 Material	合金钢 Alloy Steel
灵敏度温度影响 TC SPAN	±0.02%F.S/10℃	电缆 Cable	Length: 12m
输入阻抗 Input resistance	400 ± 20Ω		