



钢包秤、天车秤
Steel embody scale, overhead crane scale

量程(t) \ 参数	A	B	C	D	E	F	G	H	H1	H2	K	L	N
10, 15, 20, 30	390	300	210	345	180	56	29	127	107	45	M16	φ18	R80
40, 50, 60	500	395	235	445	200	86	45	173	153	67	M20	φ22	R90

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	10、15、20、30、40、50、60t	绝缘电阻 Insulation resistance	≥5000 MΩ
精度等级 Accuracy class	0.05,0.1	额定温度 Nominal Temp Range	-10~+40℃
灵敏度 Sensitivity	10~30t: 2.0±0.005mV/V	工作温度范围 Service Temp Range	-30~+70℃
	40~60t: 1.5±0.005mV/V	安全负载 Safe load limit	150%F.S
线性误差 Non-linearity	0.05%F.S,0.1%F.S	破坏负载 Breaking load	200%F.S
滞后误差 Hysteresis error	0.03%F.S	额定激励电压 Nominal of range excitation	10~12 V DC
蠕变 (30分钟) Creep(30min)	±0.02%F.S	密封等级 Protection Class	IP67
零点温度影响 TC ZERO	±0.02%F.S/10℃	材料 Material	合金钢 Alloy Steel
灵敏度温度影响 TC SPAN	±0.02%F.S/10℃	电缆 Cable Length:	8m (10t), 10m (15t)
输入阻抗 Input resistance	750±10Ω		12m (20t), 16m (30~6t)
输出阻抗 Output resistance	702±5Ω		Diameter: Φ6mm